

CROSS-SECTION PROPERTIES

Name of program: **polygon V 2.0**

This program determines for a polygonal section the center of gravity, area, moments of inertia and main moments of inertia including the angle of rotation of the main axes.

Furthermore the stresses of all input points may be calculated for any combination of N (**positive**, if acting as **tension** force), M_y and M_z . (figure 2). N may be entered as acting in the center of gravity (**default**) or any point of your choice.

Besides, the intersections of the neutral axis ($\sigma = 0$) and the polygon shape as well as the inclination γ of this axis are indicated.


Go to page 1.1 and enter all points counterclockwise (points 7 – 10 in fig. 2), missing areas have to be input clockwise (pts. 2 – 6). Make sure that the dimensions of the coordinates are consistent with the loads (e.g. **cm** and **kNcm** !). If all n points are entered, key in **x** in the next input-box for y_{n+1} (**x** stands for the letter-key x here and in all following inputs for **x** !).

The program then offers the opportunity to change points, otherwise enter **0** in the “change-box”.

Besides, the areas of circles may be subtracted, as depicted in the example of figure 1. To exit this part of input enter **x** or **0**, if the next diameter is requested.

To end the program here if there are no loads to be examined, enter x if the program prompts for the input of N.

Following now is the input of the loads in corresponding text-boxes, which results in the output of the stress values for the input points. Furthermore, a plot of the contour including the main axis for I_1 and I_2 as well as the neutral axis is provided on page 1.2, a list of all results on pages 1.3 and 1.4.



EXAMPLE

Being given the section of figure 1) and the loads $N = -50 \text{ kN}$ acting in the centre of the section; $M_y = -700 \text{ kNcm}$, and $M_z = +200 \text{ kNcm}$, calculate the stresses $\sigma_{,i}$ ($1 \leq i \leq 12$). Three circle areas, each circle having the diameter $D = 3$ and the coordinates of the centre $y_{c1} = 2.5$, $y_{c2} = 6.5$, $y_{c3} = 10.5$ and $z_c = 2.5$ have to be subtracted.


TABLE of COORDINATES ([cm]):

i	y _i	z _i	i	y _i	z _i
1	0	0	7	0	0
2	2.5	5	8	13	0
3	2.5	8.8	9	16	8.8
4	11.8	8.8	10	21	8.8
5	10.5	5	11	21	13
6	2.5	5	12	0	13


Store **"Polygon.tns"** into the MyLib-folder and start **"crossec()**" on page 1.1 of the document. On the first request enter **1** if a section is already existing and points of the section have to be changed, or **2**, if new loads are to be examined. Otherwise, as in this example, key in **0** (figure 3).

Now enter the points as indicated in the table. If the coordinate **"y-13 = "** is indicated, enter **x** to conclude this input (fig. 4). If you entered a wrong value for point i, enter now the number i in the **"Change point #i : "**-field and key in the new values, otherwise or to exit enter **0**.


The program now prompts for the input of missing areas of circles on the cross section (fig.5):



3)




4)




5)

Key in **1**, then enter D, y_c and z_c for the three circles. After each input the subtracted area of this circle is depicted as A_{c,i}. Input **0** or **x** on the prompt of the fourth circle (fig. 6).


Now the section properties A, y_s | z_s, I_y | I_z, I₁ | I₂, I_{yz} | φ are calculated. Following then are the request-boxes for the loads. If N <> 0, the input of point (y_N, z_N), N is acting in, is requested additionally. Default are the coordinates of the centre of gravity (x_s,z_s).



6)




7)




8)

Enter the **N** as given above and leave the indicated values of y_N and z_N in the screen (fig. 7), then key in the values of **My** and **Mz**.


As result **A, ys zs Iy, Iz, Izy, I1, I2** and the inclination φ of the main axis as well as all σ_i now are displayed (fig. 8 – 9) . If there is a change in sign from σ_i to σ_{i+1} , an additional line depicts the



9)



10)



11)

values y_{i-(i+1)} and z_{i-(i+1)}, where σ = 0 , as demonstrated for points 2 and 3 in figure 9. γ stands for

the inclination of the neutral axis. The last display of the result summarizes the minimum/maximum stresses on the whole section.

For a new load case enter **1** on the next request, otherwise key in **0** to quit the program.

On page 1.2 of the document you will find a plot of the section with the main axis and additionally the neutral axis γ , if you have entered loads (fig. 10). Page 1.3 depicts again the section properties, while page 1.4 gives you the coordinates of the entered points (y, z), the intersection points (y_0, z_0) between contour and neutral axis and its inclination angle γ in $^\circ$ (fig. 11). The intersection points $y_{0,i+1}$ and $z_{0,i+1}$ display the coordinates of a change of sign between σ_i and σ_{i+1} , ($\sigma=0$), otherwise \updownarrow is indicated.

HINTS and WARNINGS

- Pay attention to the applied units! If you enter the coordinates in [**cm**] and moments in [**kNcm**], stresses are output in [**kN/cm²**] !

-The number of missing circle areas is unlimited for the calculation, whereas only the first **twelve** are indicated in the graph on page 1.2 !

-For the plot the scatterplot variables s_1 and s_2 are used. Do not delete them, in case it happens, go on page 1.3, press “**menu**” **3 – 4**, open the input line and enter { $x \leftarrow yy$; $y \leftarrow zz$ in s_1 and { $x \leftarrow yss$; $y \leftarrow zss$ for s_2 .

All parts of this program are copyrighted by Claus Dachsel.

It is provided as a free release, for non-commercial purpose “as is” without warranty or responsibility of any kind. In no event will the copyright holder be liable for damages arising out of the use or inability to use this program.

Claus Dachsel

clan.dachsel@t-online.de